

AD-A081 867

GENERAL ELECTRIC CO BURLINGTON VT ARMAMENT SYSTEMS DEPT F/6 19/6
INSTALLATION STUDY OF THE GE 430 GUN IN THE AH-1G HELICOPTER.(U)
DEC 79 J M SEEMANN, T W WUENSCHEL DAAK10-79-C-0268
80APB502 NL

UNCLASSIFIED

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) (6) INSTALLATION STUDY OF THE GE 430 GUN IN THE AH-1G HELICOPTER		5. TYPE OF REPORT & PERIOD COVERED Final Technical Report 8/3/79 - IR/31/70
7. AUTHOR(s) (10) Jim M. Seemann Tom W. Wuenschel		14. PERFORMING ORG. REPORT NUMBER (14) 88APB502
9. PERFORMING ORGANIZATION NAME AND ADDRESS General Electric Co., Inc. Armament Systems Dept. Lakeside Ave., Burlington, VT 05402		15. CONTRACT OR GRANT NUMBER(s) (15) DAAK10-79-C-0268
11. CONTROLLING OFFICE NAME AND ADDRESS Commander H. Q. ARRADCOM, Dover, NJ 07801 DRDAR-SCS-T AC 201-328-3284 AV 880-3284		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS (12) 22
12. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) (9) Final technical rept 3 Aug 79 - 31 Dec 79		12. REPORT DATE (12) December 79
13. DISTRIBUTION STATEMENT (of this Report)		13. NUMBER OF PAGES 18
14. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
15. SUPPLEMENTARY NOTES		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. KEY WORDS (Continue on reverse side if necessary and identify by block number) HIGAD 430 GUN AH-1G HELICOPTER SERVO DRIVES RATE FEED FORWARD SERVO BANDWIDTH		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A study is presented of a 430 gun installed in a AH-1G helicopter and firing GAU-8 ammunition. The weight of the system limits ammunition capacity to less than 100 rounds. The forces on the helicopter limit the burst length to only a few rounds due to the stability augmentation limits of the helicopter. Concepts are generated which address the gun mount control system. Electric versus hydraulic servo drives are discussed. The effects of fire rate on servo bandwidth are studied as are the effects of angular base motion of the helicopter.		

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

403584

50B

TABLE OF CONTENTS

<i>Title</i>	<i>Page</i>
SUMMARY	1
INTRODUCTION	2
TECHNICAL DISCUSSION	3
Mechanical Systems	3
Helicopter Weight and C.G. Limitations	3
Static and Dynamic Loading in the Mounting Area AH-1G	3
Structural Limitations	
Limited Turret Field of Fire	5
Gun Recoil Loads — Recoil System Design	5
Gun Mount Balance	6
Servo Design Considerations	6
Electric Versus Hydraulic Servo Drives	7
Torque Response Requirements	7
Base Motion Response Requirements	7
Servo Loop Design	8
CONCLUSIONS AND RECOMMENDATIONS	12
REFERENCES	13
APPENDIX A	A-1

Accession For	
NTIS GCAI	<input checked="" type="checkbox"/>
DDC TAB	<input type="checkbox"/>
Unpublished	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability	
Dist	Available on special
A	

SUMMARY

The system identified in this study is intended mainly as a test vehicle that would verify feasibility, and provide data for further development of this concept.

A trainable gun concept with limited field of fire is presented that weighs about 1100 lbs, and is located aft of the 20-mm turret occupying the former ammunition compartment. Ammunition capacity is less than 100 rounds. Power for the system would come from a stored energy source such as an accumulator. The field of fire is $\pm 10^\circ$ azimuth, $+6^\circ$ and -10° in elevation, for short bursts only, depending on the gun elevation. The servo system utilizes linear hydraulic actuators connected to elevation and azimuth gimbals and a balanced gun cradle. Elevation and azimuth servos are essentially the same. Each servo has electronic tach and position loops. Loop bandwidths were selected to attenuate the instantaneous torques generated by the vertical and horizontal gun support loads. This approach reduces weight and power consumption. Dynamic pointing accuracy is maintained by having a balanced gimbal, low inertia drive system and incorporating rate feed forward into the servo system.

INTRODUCTION

There is an interest in some quarters for arming an attack helicopter with a gun system capable of defeating armored targets. This study is the result of a proposal by the General Electric Company to analyze the requirements of such a high impulse gun system, and perform tradeoff studies to identify a suitable turret design.

A contract was awarded to GE in August 1979 to study the effects of loads and torques on the helicopter airframe and turret.

This study addresses the concepts specifically outlined in the Statement of Work, and further separates them into two general categories of Mechanical Systems and Servo Design Considerations. The work done under this contract was accomplished by analysis of system performance and functional requirements, and identification of a system configuration compatible with those requirements.

The GAU-8 ammunition considered in this study is a high impulse round (125-150 lb-sec), with an effective antiarmor projectile (APIT). The GE 430 gun used as a test vehicle in this concept is a 4-barrel, 30-mm gatling gun developed by General Electric, and currently used in the GEPOD 30.

The objective of the study was to determine if GAU-8/A ammunition could be successfully fired in a GE 430 gun from the AH-1G helicopter. The conclusion of the study is, that while it is feasible, only a few rounds could be fired in a burst, due to stability augmentation limits of the helicopter. Further study is needed to determine the effectiveness against the intended target.

Future studies should include detail simulations of the helicopter airframe and gun servos. These simulations would provide information on the helicopter airframe vibrations as a result of firing the GE 430. This would be done with various firing rates, burst length, recoil systems and gun control systems.

TECHNICAL DISCUSSION

MECHANICAL SYSTEMS

Helicopter Weight and C.G. Limitations

This concept is based on the assumption that the weight of the HIGAD installation aboard the AH-1G should not exceed the fully loaded XM97 system weight (1002 lbs), and the c.g. should be no further forward than the c.g. of the fully loaded XM97 (F. STA 101.5). (See Appendix A.)

This weight and c.g. limitation locates the gun in the aircraft, and has a significant impact on the structure, ammunition capacity, gun drives, servo actuators, and recoil system. The center of gravity of the gun and cradle should be located as near as possible to the fuselage station 101.5 (the c.g. of a loaded XM97 system), while allowing clearance for maximum recoil motion between the aft end of the gun, and the bulkhead at fuselage station 138.7. The HIGAD gun would occupy the ammunition compartment space on the AH-1G, Figure 1. The structure will have to be an efficient, lightweight design to meet the weight limitation. Since there is no space available at the aft end of the gun, ammunition storage will have to be at the side or bottom of the gun. This concept allows a closed loop of ammunition of less than 100 rounds for test purposes. The tradeoff of gun drives will be made largely on space and weight. If there is insufficient electrical or hydraulic power available to drive the 430 gun (6 hp at steady state - 6 times the XM197 power), then the power will come from a stored energy source; accumulator, batteries or compressed gas located near the helicopter c.g. A dc motor drive and battery pack were included in the weight and c.g. analysis. The tradeoff study of gun drives and energy storage should be the subject of future analysis.

Static and Dynamic Loading in the Mounting Area AH-1G Structural Limitations.

The only structural portion of the XM97 turret that might be applicable in a HIGAD installation is the upper support and azimuth bearing. There is not enough depth or clearance in the lower support to contain a 430 gun and cradle (saddle). Since the upper support has inadequate fatigue life for peak recoil loads exceeding 2000 lbs at the present XM197 location, it is unlikely that the upper support would be structurally adequate for a 430 HIGAD installation.¹ The average (rms) recoil force for both active and passive recoil attenuators will be 1680 lbs at 720 spm, however, the active system could reduce the peak-to-peak forces, resulting in a lower maximum recoil force. (See Appendix A.) The maximum vertical forces at the gun supports will be approximately the same for either recoil system, due to the fact that both systems set back and dither approximately the same. The firing barrel location relative to the structure and azimuth bearing, results in significantly larger stresses of the upper support and bearing. A new structure should be designed which would allow a mounting area interface with the AH-1G large enough to dissipate the recoil loads and moments safely, and minimize local deflections of structure which may affect accuracy. In addition, extensive modifications of the bulkhead aft of the existing turret would be required for clearance of the gun which extends aft of the bulkhead.




Figure 1. HIGAD 430 AH-1G Gun Installation — Mechanical Schematic

THIS PAGE IS BEST QUALITY PRACTICABLE
FROM COPY FURNISHED TO DDC

One method of reducing the structural loads is by the use of a muzzle brake which could reduce the recoil loads by about 20%. Such a muzzle brake device is currently in use on the GE 30-mm pod. These devices tend to aggravate gun gas flash and pressures in the vicinity of the muzzle, and may not be suitable for this application.

Limited Turret Field of Fire

It will be assumed that the HIGAD turret field of fire will be limited by the AH-1G rotor torque capability to correct for moments about the c.g. of the helicopter. Those rotor torques are:

Roll	4400 ft-lbs	These numbers were obtained from Bell Helicopter
Pitch	2500 ft-lbs	
Yaw	8900 ft-lbs	

This assumption is based on steady state continuous firing using average recoil loads.

The yaw and roll moments due to firing the 430 gun at 720 spm in the 10° maximum train position are 2430 and 1170 ft-lbs respectively, well within the control limits of the helicopter. However, the average pitch moment due to firing the 430 at the 720 spm rate exceeds the 2500 ft-lbs allowable, except at depression angles of 17° and lower. (See Appendix A.) Those large depression angles are beyond the scope of this study, and would require other concepts of mounting and controlling the gun. At a reduced firing rate of 360 spm the gun may be depressed to 7° and lower without exceeding the control limit. Another helicopter control factor to be considered is the total thrust aft if the rotor is used to its maximum pitch correction while the gun is firing. At the high rate of fire this thrust amounts to 1680 lbs from the gun, which added to the compensating rotor thrust would amount to a significant deceleration of the helicopter.

These high loads and moments nearly preclude firing continuously, and the length of burst would be limited by the controllability of the helicopter and maintaining accuracy of the gun within the limitations of the sight and gun control systems. If the gun is fired at depression angles less than 17° the length of burst is limited by the gun reaching the maximum elevation position (+6°) as the helicopter pitches down. (See Appendix A.)

Gun Recoil Loads - Recoil System Design

The gun recoil peak-to-peak loads should be kept to a minimum to minimize the disturbance of firing to the aircraft which may affect gun pointing accuracy.

In general, the recoil forces are higher at higher rates, but the ratio of peak-to-peak forces is less. For instance, the Honeywell active recoil system varies from a peak of 1760 lbs at 720 spm to only 960 lbs at 360 spm, while the maximum peak to minimum peak ratio of recoil forces varies from

1.21 at 720 spm to 1.52 at 360 spm. The GE passive recoil system has a maximum peak of 3300 lbs and peak-to-peak ratio of 4.71.

While an active recoil system has potential in improving accuracy and increasing structure fatigue life by reducing peak-to-peak loads, it will add considerable weight and cost to the system. Peak hydraulic flow rates of approximately 47 gpm (1500 psi - 3 inch stroke) will be required, which will require a power supply to deliver more than 20 hp. Since there is insufficient hydraulic power available on the AH-1G, an energy reservoir system must be included, such as an hydraulic accumulator. The size, weight, and placement of these components have not been included in this analysis, but should be included in future tradeoff studies of a recoil system design.

The size and weight of a typical low force, passive ring spring recoil system were included in this analysis. Our experience with similar turreted systems on XM97 and EX-83 indicates that such recoil systems provide adequate peak-to-peak force reduction at significant savings of weight and cost.

The effect of the moment due to the offset between the firing barrel and the center of gravity of the guns' recoiling mass can best be improved by optimizing the supporting stiffness in the plane of the moment. This can allow more gun motion in this plane, reducing the forces and the resulting disturbance on the servo control system.

A major factor affecting location of the firing barrel and the center of gravity of the recoiling mass is the type of ammunition feed chuting and its location. A rigid chuting mounted outboard of the gun will be accelerated more than 100 g's with each round fired, will be subjected to very high stresses, and will adversely affect the c.g. of the recoiling mass and create higher transverse forces due to the moment induced by gun longitudinal accelerations. A flexible ammunition chuting which allows less rounds and chuting to move through the entire gun range of motion will reduce stresses on gun, feeder, and chuting and have less adverse effect on the c.g. and transverse forces. The location of the firing barrel will be determined by the size and flexibility of the chuting. The weight and c.g. limitations dictate that less than 100 rounds can probably be stored directly opposite the gun feeder, to either side of or below the gun.

Gun Mount Balance

The average disturbance torques should be kept low by locating the fore-aft c.g. and the firing barrel as close as possible to the gimbal axes.

SERVO DESIGN CONSIDERATIONS

The primary function of the gun servo system is to keep the gun aligned with the commanded position from the fire control system in the presence of torque disturbances and dynamic motion of the helicopter. The following considerations were addressed in this study.

Electric Versus Hydraulic Servo Drives

For the limited field of fire of $\pm 10^\circ$ in azimuth and $+6, -10^\circ$ in elevation; linear actuators provide an efficient package. Hydraulic actuators were selected because hydraulic systems are capable of producing larger torque than electrical equipment of equivalent sizes or weights. As detailed later, the maximum flow required is estimated at 5 gpm at 1500 psi.

Torque Response Requirements

The 430 gun is a 30-mm 4-barrel Gatling gun. With this type of design, the center of gravity of the recoiling parts is approximately in the geometry center of the circle formed by the four barrels. The 430 has its firing barrel 2.8 inches from the center of gravity of the recoiling parts. Firing the gun will produce moment impulses within the recoiling parts. The major concern is not pointing errors or dispersion due directly to the firing disturbance. These are normally insignificant with proper gun mounting (firing barrel on axis). The cyclic gun position error signals due to the firing disturbance is not a true measure of the gun pointing error (i.e. where the bullets will go). The fundamental component of the errors is the firing frequency. Thus, for a constant firing rate, the gun error is approximately the same at each instant the round is fired. For this reason it is not required to have the servos respond to the firing instantaneous disturbance. If the servos were to respond and try to keep the gun from moving, the servo power consumption, during firing, would be significantly increased. Tracking performance can be reduced because available power was reduced in overcoming these disturbances. Thus, in order to keep the servo components small and lightweight and minimize power consumption, it is desirable to design the servo control so that it does not respond to the instantaneous firing disturbances.

One method for achieving this torque response, is to have the servo bandwidth lower than the firing rate. Disturbance torques become more of a problem at low firing rates. In this study, the maximum firing rate of the GE 430 is primarily determined by the stabilization capabilities of the helicopter during firing. The rate loop bandwidth is set at approximately 40 rd/sec to reduce the response to the firing disturbance at 75 rd/sec.

Base Motion Response Requirements

Helicopter base motion will disturb the servo system as "(S θ) helicopter" shown as the servo block diagram. Both low frequency (less than 1 Hz) motion due to evasive maneuvering or air turbulence and high frequency motion resulting from vibrations are present. Normally, the low frequency motion is the significant base motion disturbance. It is assumed that the servo position command signal will be stabilized but the errors required to drive the rate loop would be appreciable in trying to follow this motion. This is especially true since the servo bandwidths were reduced in order to obtain the desired torque response. To effectively eliminate the errors due to base motion, rate feed forward would be used. This signal is now available on the AH-1G Multi-Weapon Fire Control System helicopter. The required gyros were added for the air-to-air gun application tests which were recently completed.

The helicopter length results in a large moment of inertia about the pitch axis, thereby minimizing the disturbances and accelerations about this axis. The average pitch acceleration at 0°

gun elevation is -0.3 rd/sec^2 (See Appendix A). There will be alternating peaks about this mean, with the maximums and minimums determined by the type of recoil system and the amount of force attenuated by the turret structure. The disturbance is at the firing frequency (12 Hz). Other disturbances can result from local deflections at the turret-helicopter interface and may have higher frequency components.²

Servo Loop Design

Figure 2 is a model of the first order effect of the gun and cylinder interaction. The gun inertia is shown as J_2 and the stiffness of the gun and support structure is shown as k .




Figure 2. First Order Effect of the Gun and Cylinder Interaction

The gimbal inertia is shown as J_1 which is driven with a double-ended hydraulic cylinder controlled by a flow control valve. Test data on the GE 430 gun shows that J_2 and k give a natural frequency of 18 Hz. The compressibility of the hydraulic fluid in the cylinder along with the aircraft structure is another spring in the system. The compressibility of the hydraulic fluid together with the cylinder design will give a linear stiffness of approximately 285,000 lbs/in. The aircraft structure is assumed to have a stiffness of 50,000 lbs/in. The total compliance (λ) is 23.5×10^{-6} lb/in. This design will allow the closure of a 40 rd/sec tachometer loop and provide the desired torque response. This design approach (balanced gimbal-train and elevation, plus firing barrel aligned with gimbal axis) minimizes the need for a high gain (bandwidth) torque response loop.

Both elevation and azimuth servos are essentially the same. The cylinders are supplied with hydraulic fluid from a flow control valve. The valve armature is driven by an electronic current loop of high bandwidth (greater than 500 Hz). The servo-valve transfer function is represented in the servo block diagram by a simple first order expression. This expression is adequate for the frequency range of interest, i.e. to about 70 Hz.

Gimbal rate relative to the helicopter is sensed by a tachometer and summed into the servo electronics. Within the tachometer servo loop electronics is an integrator to allow closure of the loop around the non-linear actuator loop. Also included is a velocity/position limit function for braking at the end of travel. The gimbal position relative to the helicopter is sensed by a position transducer. Within the forward part of the position loop electronics there is an integrator-lead function in addition to synchronizing circuits. The position loop bandwidth would be approximately 1 Hz. The function of the integrator-lead function is to ensure zero static position errors in response to steady-state torque disturbances such as wind load. The static error is then a function of transducer accuracy, servo deadband and amplifier offsets.

It can be shown by block diagram (Figure 3) manipulation that the effective position bandwidth with rate feed forward is the product of the two loop bandwidths. For this preliminary design, the effective position loop bandwidth for command inputs is $6 \times 40 = 240$ rd/sec. This high effective bandwidth will allow the gun servo to follow command inputs to less than one milliradian.

The position and rate feed forward command signals may be digital or analog. Digital inputs would be converted to analog voltages with standard D/A modules.

The torque requirements for the GE 430 servo are conservatively estimated to be 1440 ft-lbs. This will provide approximately the same peak acceleration capability as the present XM97 turret. The limited field of fire (10°) compensates for the larger area of the GE 430 so that the maximum wind load is about the same as the XM97 turret. A piston area of 2.0 in.² and a one foot lever arm were selected. With a supply pressure of 1500 psi, the normal load pressure will be less than a half of the supply pressure. This will help linearize the rate loops. A Moog series 32 servo valve was selected. With this valve, a hydraulic flow rate of 18.8 in.³ sec. (5 gal/min) will drive the gun system at 45° /sec.

The servo bandwidths were determined primarily from two factors: the maximum firing rate is set by the helicopter torque limits; and the tach loop bandwidth must be less than the firing frequency in order to reduce the response to firing torques.

The preliminary design has a tach loop bandwidth of 6 Hz which is set with the gain term K_2K_V . The position loop bandwidth is 1 Hz, set with K_1 .




Figure 3. Hydraulic Servo Block Diagram

ESTIMATED SERVO LOOP PARAMETERS

J_1	GIMBAL INERTIA	11 SLUG FT ²
J_2	GUN INERTIA	61 SLUG FT ²
K	GUN STIFFNESS	800,000 FT-LB/RAD
C	GUN DAMPING	4000
A	PISTON AREA	2 IN. ²
R	LEVER ARM	1 FT
μ	FLOW/PRESSURE GRADIENT	0.13 CIS PSI MAX.
L	$\lambda \cdot A^2$	
λ	HYDRAULIC & STRUCTURE COMPLIANCE	23.5×10^{-6} IN LB
$K_2 K_V$	TACH LOOP GAIN	SET FOR BANDWIDTH OF 6 HZ
K_1	POSITION LOOP GAIN	SET FOR BANDWIDTH OF 1 HZ

CONCLUSIONS AND RECOMMENDATIONS

This study concludes that the concept of a high impulse gun firing from a helicopter is feasible with limitations on burst length and requiring extensive structural modification. Further analysis is required to determine the adequacy of the system effectiveness.

The dynamic gun pointing errors should be determined from a simulation of the recoil forces on the helicopter airframe and gun servos.

The design configuration will require further analysis and tradeoff studies for recoil system, drive, power supply and structural design.

REFERENCES

1. D.H. Spawn, *Advanced Turret Study*, Technical Information Series No. 79APB509, Burlington: General Electric Armament Systems Department, 9 January 1979.
2. T.D. Hutchings and A.R. Zak, *The Investigation of Dynamic Gun Pointing Errors for Helicopter Mounted Automatic Cannon Systems*, Rock Island: GEN Thomas J. Rodman Laboratory, 2 November 1976.

APPENDIX A
SYSTEM ANALYSES


WEIGHT AND C.G. ANALYSIS HIGAD VS XM97

XM-97	Component	Weight (lbs)	c.g. from AZ axis STA 75.5 \bar{X} (in.)
	XM197 Gun	179	-3.45 (meas.)
	Turret Assembly	175	
	Feed System	93	+43.2 (est.)
	750 Rounds 20-mm Ammo	421	
	750 Links	106	
	Control Electronics	29	+16 (est.)
	Loaded System	1003	+26 STA 101.5
	Empty System	582	+13.5 STA 89

430 HIGAD	Component	Weight (lbs)	c.g. from recoil attachment (in.)
	430 Gun & Feeder	360 (meas)	-11.2
	Drive Motor & Gearbox	27	-11.2 (est)
	Servo Actuators	9	
	Recoil Adapters	25	
	Gun-Servo Control Electronics	29	
	Structure (cradle, Az & El yoke & drive support)	369	35% of volume in steel
	GAU-8 Ammunition 80 rds	120	+16
	Ammunition Conveyor & Storage	64	
		1003	-6.2
	Gun Drive Battery Pack	80	Assumed located at c.g. of helicopter

if 430 gun c.g. is at STA 101.5 locate recoil attachment at STA 101.5 +6.2 or STA 106.7

HIGAD RECOIL LOAD ANALYSIS PREDICTED DATA




HIGAD RECOIL LOAD ANALYSIS

PITCH, ROLL, AND YAW MOMENTS ABOUT cg OF AH-1G

ASSUME IMPULSE OF GAU-8 30-MM I = 140 LB-SEC

AVERAGE RECOIL LOAD = AT 720 SPM $\bar{F}_{720} = \frac{720 \cdot 140}{60} = 1680 \text{ LBS}$

AT 360 SPM $F_{360} = 840 \text{ LBS}$



MAX PITCH MOMENT $M_p = \bar{F}_{720} r_{\max} = 1680 \text{ LBS} \frac{58.2 \text{ FT}}{12} = 8146 \text{ FT-LBS}$
 AT $\theta = +6^\circ$ $r = 58.2 \text{ IN}$

AT 360 SPM $M = 840 \text{ LBS} \times \frac{58.2}{12} \text{ FT} = 4073 \text{ FT-LBS}$

SAFE GUN ELEVATION WHEN $M_{SCAS} = 2500 \text{ FT-LBS}$ $r_{\text{safe}} = \frac{2500}{1680 \text{ LBS}} \text{ FT-LBS} = 1.5 \text{ FT}$


$\theta_{\text{safe}} = -25.6^\circ + \sin^{-1} \left(\frac{r}{110.9} \right)$ $\theta_{\text{safe}} = -16.4^\circ$

AT 360 SPM $\theta_{\text{safe}} = -25.6^\circ + \sin^{-1} \left(\frac{2500/840}{110.9/12} \right) = -6.8^\circ$

MAX ROLL MOMENT $M_R = \bar{F}_{720} r_R \sin 10^\circ = 1680 \text{ LBS} \frac{48 \text{ FT}}{12} \sin 10^\circ = 1167 \text{ FT-LBS}$

MAX YAW MOMENT $M_Y = \bar{F}_{720} r_Y \sin 10^\circ = 1680 \frac{100 \text{ FT}}{12} = 2431 \text{ FT-LBS}$

PITCH MOMENTS AT VARIOUS GUN ELEVATIONS AND FIRING RATES



AH-1G RESPONSE TO HIGAD

$$J_{\text{PITCH}} = 14,000 \text{ SLUG FT}^2 \text{ (FT-LBS SEC}^2\text{)}$$

TORQUE FROM FIRING GUN AT A CONSTANT 0° ELEVATION

$$r_p = 4 \text{ FT}$$

$$\bar{F}_{720} = 1680$$

$$T_p = -8720 \text{ FT-LBS (}$$

$$\text{SCAS } T_{\text{SCAS}} = +2500 \text{ FT-LBS)}$$

HELICOPTER
PITCH
ACCELERATION

$$\alpha_p = \frac{T}{J_p} = \frac{-8720 + 2500 \text{ FT-LBS}}{14,000 \text{ FT-LBS SEC}^2} = \frac{-0.3 \text{ RAD}}{\text{SEC}^2} = -17.3^\circ/\text{SEC}^2$$

$$\omega_p = \omega_0 + \alpha_p t, \quad \theta_p = \omega_0 t + \frac{1}{2} \alpha_p t^2$$

WITH SCAS

AT 1 SEC $\omega_p = -17.3^\circ \times 1 = -17.3^\circ/\text{SEC}$ $\theta_p = \frac{1}{2} 17.3^\circ/\text{SEC}^2 \times 1^2 = -8.65^\circ$ GUN WOULD HIT ELEVATION STOP AT $+6^\circ$ ELEVATION IF IT REMAINED TRAINED ON TARGET.

AT 2 SEC $\omega_p = -34.6^\circ/\text{SEC}$ $\theta_p = -34.6^\circ$

